



**ACE 1500**

OPEN PLATFORM LIFT

MADE IN EU





## ACE 1500

### Open Platform Lift

**ACE 1500** is a Open Platform Lift, also known as Wheelchair Lift, which provides internal or external vertical travel up to 3 meters. Our Open Platform Lift can accommodate changes in level from 600 mm up to 3000 mm in commercial and domestic environments and is appropriate alternative solution to a fully enclosed platform lift.

ACE 1500 is specifically designed for applications with little or no alterations to existing buildings. The open type

design offers an aesthetically pleasing solution with brushed stainless steel finish as option. The lift provides a safe and easy way to gain access to a property where stairs would otherwise prevent wheelchair access.

It is designed to give customers choice and flexibility.

ACE 1500 Wheelchair Lift is a space saving and cost effective way to provide access for everyone to your home or workplace.

All our lifts are supplied with a 24-month warranty, as standard, and we offer a range of maintenance and service options, which can be tailored to suit your specific requirements.

## FEATURES

- MODERN LIGHTWEIGHT DESIGN
- STAINLESS STEEL CONSTRUCTION AS OPTION
- LOW SPACE REQUIREMENTS
- HIGH LEVEL OF SECURITY
- SILENT OPERATION
- SIMPLE TO USE
- NO PIT REQUIRED
- SIMPLE TO INSTALL AND EASY TO SERVICE
- OVERALL LOW MAINTENANCE AND RUNNING COSTS



Our **Mechanical emergency fall brake for elevator** technology is under patent protection process at International level, i.e.: it has patent pending status in Lithuania Patent State Bureau and in World Intellectual Property Organization (WIPO).

## SPECIFICATIONS

User group	Ambulant and wheelchair users
Suitability	For internal or external use
Travel	From 600 mm up to 3000 mm
Number of stops	2
Maximum capacity	400 kg
Platform size	1100 x 1400 mm (standard)
External dimensions	1300 x 1770 mm (standard)
Gate	950 x 1100 mm (standard) with auto closers
Cabin height	1100 mm
Drive type	Belt
Power	220-240 V, 1 phase, 16A 380-400 V, 3 phase, 10A, 50 Hz
Lighting	Controls illuminated
Safety edge	Safety edge-under platform proximity sensors
Handrail	Integrated to lift cabin (on both sides)
Machine room	Integral to guide rails
Floor	Anti slip rubber (Anti slip diamond plate for outdoor version)
Finish	RAL 9006 (White aluminium)

## OPTIONS

<b>PLATFORM</b>
900 x 1400 mm 1000 x 1400 mm
<b>GATE</b>
Automatic upper gate Automatic lower gate
<b>CONTROL</b>
Configurable control side Dual control on the platform Auto dialer on the platform Remote control Braille on the control
<b>SAFETY</b>
Automatic emergency lowering device
<b>FINISH</b>
Painted in any RAL color Brushed Stainless Steel



WE ARE CONSTANTLY THINKING ABOUT TOMORROW, BECAUSE WE KNOW THAT THE SUCCESS BELONGS TO THOSE WHO BEST PREDICTS THE NEEDS OF CUSTOMERS. WE LOVE CHALLENGES. WE ARE READY TO FULFILL CUSTOMER ORDERS FASTER THAN OTHERS AND FULFILL ORDERS THAT OTHER COMPANIES DO NOT DARE TO TAKE.



1. *What is the main purpose of the document?*  
2. *What are the key findings of the study?*  
3. *What are the implications of the research?*  
4. *What are the limitations of the study?*  
5. *What are the future research directions?*